

FULL HEIGHT TURNSTILE GATE- DOUBLE - NW-FH-01

Features of Full Height Turnstile Gate - Single - NW-FH-01

- ✔ Full Height Turnstile Gate with single or bi-directional.
- ✔ Prevent anti-directional access, access granted and allow to pass through one direction at a time, the other side will remain lock; the timing can be configured.
- ✔ Self-resetting function will allow the turnstiles to lock when there's no passenger passes through.
- ✔ Programmed Fail Safe or Fail Secure Mode.
- ✔ LED Directional indicator function to display authorize passage on both direction.
- ✔ Equipped with Micro-Controller board with counting function using LED digital display (Optional).
- ✔ Equipped with Micro-Controller board with memory function for group access (Optional)
- ✔ Seamless entry upon receiving control signal, using optical hole focus technology.



Singapore

Singapore : www.smarttouch.com.sg



Office : +(65) 6396 4767 /
Mr. kenny : +(65) 9088 4767
Mr. Marco : +(65) 8122 0804
Email : sales@smarttouch.com.sg

Malaysia

Malaysia : www.smarttouch.com.my

Office : +607-388 9903
Mr. Kenny : 012-7883383
Email : sales@smarttouch.com.my

FULL HEIGHT TURNSTILE GATE- DOUBLE - NW-FH-01

Specification of Full Height Turnstile Gate- Double - NW-FH-01

Description	Parameter
Power Voltage	AC220+10%,50Hz
Drive Voltage	AC12V+AC18V
Open Angle	90°/120°
Pass Speed	Less than 30 person/minutes
Structure	Frame on 304 Stainless Steel Cover
Open Direction	Single / Double (Bi-directional)
Work Environment	Indoor / Outdoor
IP Rating	IP43
Width of Passage	<630mm
Length of Bar	600mm
Operation Condition	-15°C – 60°C
Relative Humidity	Non-Condensation
Service Life	> 6 million
Input Signal	12V DC
Working Current	<2000mAh
Dimension	1600 x 1500 x 2300mm (Long*Width*Height)



Singapore

Singapore : www.smartouch.com.sg

Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

Email : sales@smartouch.com.sg

Malaysia

Malaysia : www.smartouch.com.my

Office : +607-388 9903

Mr. Kenny : 012-7883383

Email : sales@smartouch.com.my