

## HIK VISION DS-K3G501SX TRIPOD TURNSTILE

The DS-K3G501 series tripod barrier is designed to detect unauthorized entrance or exit. By adopting the turnstile integratedly with the access control system, person should authenticate to pass through the lane via presenting IC or ID card, scanning QR code, etc. It is widely used in attractions, stadiums, construction sites, residences, etc.

### Features of HIK VISION DS-K3G501SX Tripod Turnstile

- ✓ Barrier open/closed, free accessing, forbidden mode are selectable
- ✓ Bidirectional (Entering/Exiting) lane
- ✓ Remote control and management
- ✓ Online/offline operation.
- ✓ Fire alarm passing



#### Singapore

Singapore : [www.smartouch.com.sg](http://www.smartouch.com.sg)  
Office : +(65) 6396 4767 /  
Mr. kenny : +(65) 9088 4767  
Mr. Marco : +(65) 8122 0804  
Email : [sales@smartouch.com.sg](mailto:sales@smartouch.com.sg)

#### Malaysia

Malaysia : [www.smartouch.com.my](http://www.smartouch.com.my)  
Office : +607-388 9903  
Mr. Kenny : 012-7883383  
Email : [sales@smartouch.com.my](mailto:sales@smartouch.com.my)

## HIK VISION DS-K3G501SX TRIPOD TURNSTILE

### Specification HIK VISION DS-K3G501SX Tripod Turnstile

| Description         | Parameter   |
|---------------------|---|
| MCBF                | > 3 million times   |
| Card Capacity       | 60,000  |
| Event Capacity      | 180,000   |
| Throughput          | More Than 35 persons per minute The actual throughput is affected by the person passing rate and passing method                       |
| Card Type           | EM,M1   |
| Weight              | Without package: 45kg (99.2 lb) With package: 69kg (152.1 lb)   |
| Approval            | CE/FCC/CB/RoHS/REACH/WEEE   |
| Lane Width          | 550 mm  |
| Module Selection    | YES   |
| Authentication Mode | Card, Face, Fingerprint, QR code  |
| Power Supply Method | 100 to 240 VAC; 50 to 60 Hz   |
| Working Temperature | -20 C – 65 C (-4 F to 149 F)  |
| Working Humidity    | 0% – 95%(no condensing)   |
| Dimensions          | Without package: 232 mm × 960 mm × 1208 mm (9.1" × 37.8" × 47.6")<br>With package: 390 mm × 1185 mm × 1320 mm (15.4" × 46.7" × 52.0") |
| Barrier Material    | Stainless steel pipe  |



#### Singapore

Singapore : [www.smartouch.com.sg](http://www.smartouch.com.sg)  
 Office : +(65) 6396 4767 /  
 Mr. kenny : +(65) 9088 4767  
 Mr. Marco : +(65) 8122 0804  
 Email : [sales@smartouch.com.sg](mailto:sales@smartouch.com.sg)

#### Malaysia

Malaysia : [www.smartouch.com.my](http://www.smartouch.com.my)  
 Office : +607-388 9903  
 Mr. Kenny : 012-7883383  
 Email : [sales@smartouch.com.my](mailto:sales@smartouch.com.my)