

## HALF HEIGHT SWING BARRIER GATE - ST-SW-03

### Features of Half Height Swing Barrier Gate - ST-SW-03

- ✓ Anti-Pinch mechanical structure, anti-bumps function, when the swing arm reset process meet resistance, within a limited time automatically stops the motor, the default delay after the reset again (until reset), and the force is very small ( $\leq 2\text{Kg}$ ).
- ✓ Anti-intrusion function, when the gate signal is not received, the arm will locked automatically.
- ✓ With automatic reset function, after the barrier gate opening, within a specified period of time not pass, the system will automatically cancel the user's access Permissions.
- ✓ Adjustable normally open or normally closed, in order to meet the requirements of different venues.
- ✓ Compatible with a most reader device, integrate via dry contact signal.
- ✓ Unidirectional or bidirectional control of personnel access. Remote control and management by the management computer.
- ✓ Fail-Safe mode to meet fire safety requirements



#### Singapore

Singapore : [www.smartouch.com.sg](http://www.smartouch.com.sg)  
Office : +(65) 6396 4767 /  
Mr. kenny : +(65) 9088 4767  
Mr. Marco : +(65) 8122 0804  
Email : [sales@smartouch.com.sg](mailto:sales@smartouch.com.sg)

#### Malaysia

Malaysia : [www.smartouch.com.my](http://www.smartouch.com.my)  
Office : +607-388 9903  
Mr. Kenny : 012-7883383  
Email : [sales@smartouch.com.my](mailto:sales@smartouch.com.my)

## HALF HEIGHT SWING BARRIER GATE - ST-SW-03

### Specification of Flap Barrier Gate - ST-SW-03

Description	Parameter
Power Voltage	AC220+10%,50Hz
Drive Voltage	AC24V5A
Open Angle	90°
Pass Speed	Less than 35 person/minutes
Structure	Frame on 304 Stainless Steel Cover
Open Direction	Single / Double (Bi-directional)
Work Environment	Indoor / Outdoor
IP Rating	IP43
Width of Passage	<550mm
Length of Bar	600-900mm
Operation Condition	-15°C – 60°C
Relative Humidity	95% Non-Condensation
Service Life	> 5 million
Input Signal	12V DC
Working Current	<2000mAh
Dimension	1600 x 180 x 990mm (Long*Width*Height)



#### Singapore

Singapore : [www.smartouch.com.sg](http://www.smartouch.com.sg)



Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

Email : [sales@smartouch.com.sg](mailto:sales@smartouch.com.sg)

#### Malaysia

Malaysia : [www.smartouch.com.my](http://www.smartouch.com.my)

Office : +607-388 9903

Mr. Kenny : 012-7883383

Email : [sales@smartouch.com.my](mailto:sales@smartouch.com.my)