

BIOMETRIC FACIAL HIK VISION 70T

SMARTFACE – 70T face recognition terminal is a kind of attendance & access control device integrated with temperature screening function. It can fast taking skin-surface temperature and upload abnormal temperature event to the center, which can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

Features of Biometric Facial HIK Vision 70T

- ✔ Uses Vanadium Oxide uncooled sensor for body temperature detection
- ✔ Temperature range: 30 °C to 45 °C, accuracy ± 0.5 °C
- ✔ Recognition distance: 0.5 to 1.5 m
- ✔ Mask alerts:
 - With mask: Voice reminder, access allowed
 - Without mask: Voice reminder, access denied (forced mode)
- ✔ Displays temperature on screen during authentication
- ✔ Data import/export and transmission via TCP/IP to client software
- ✔ Supports 6 attendance statuses: check in, check out, break in, break out, overtime in, overtime out



Singapore

Singapore : www.smartouch.com.sg

Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

Malaysia

Malaysia : www.smartouch.com.my

Office : +607-388 9903

Mr. Kenny : 012-7883383

BIOMETRIC FACIAL HIK VISION 70T

Specifications of Smart Face Recognition - 70T

Screen	7 inch touch screen
Card capacity	6,000
Event capacity	100,000
Face capacity	6,000
Face recognition distance	0.5 to 1.5 m
Face recognition duration	< 0.2 s per person
Interface	Network × 1, RS-485 × 1, Wiegand × 1, Lock output × 1, door contact input × 1, exit button × 1, tamper × 1
Camera	2 MP dual-lens camera, WDR
Card reading duration	< 1 s
Card reading distance	0 to 5 cm
Working humidity	10 to 90% (No condensing)
Working temperature	0 °C to 50 °C (32 °F to 122 °F) For temperature measurement: 10 °C to 35°C (50 °F to 95 °F)
Power supply	12 VDC/2 A
Recognition mode	Face: 1:1 and 1:N
Temperature Range	30 °C to 45 °C (86 °F to 113 °F)
Temperature accuracy	±0.5 °C, without black body calibration
Measuring distance	0.3 to 2 m
Frame rate	25 fps
Sensor	Vanadium Oxide uncooled sensor



Singapore

Singapore : www.smarttouch.com.sg



Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

Malaysia

Malaysia : www.smarttouch.com.my

Office : +607-388 9903

Mr. Kenny : 012-7883383