

FACE RECOGNITION TERMINAL - ST673

Face recognition terminal is a kind of access control device. It can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

Features Pro Face Access Terminal - ST673

- ✓ 7-inch LCD touch screen, 2 Mega pixel wide-angle lens
- ✓ Recognition distance: 0.3 to 3 m
- ✓ Face recognition duration < 0.2 s/User
- ✓ Built-in M1 card, Felica card, and DESfire card reading module (Presents card on the screen to authenticate)
- ✓ Face mask detection
- ✓ 100,000 face capacity, 10,000 fingerprint capacity (With fingerprint module), 500,000 card capacity, and 150,000 event capacity
- ✓ Supports ISAPI, ISUP 5.0, TCP/IP (IPv4 and IPv6)
- ✓ Supports single person and multiple people (Up to 5 people) recognition



Singapore

Singapore : www.smarttouch.com.sg

Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

Malaysia

Malaysia : www.smarttouch.com.my

Office : +607-388 9903

Mr. Kenny : 012-7883383

FACE RECOGNITION TERMINAL - ST673

Specifications of Face Recognition Terminal - ST673

| | |
|---------------------------------------|--|
| Operating system | Linux |
| Size | 7-inch |
| Type | Touch screen |
| FOV | HFOV= 75.5°; VFOV= 41.5°; DFOV= 87° |
| Pixel | 2 MP |
| Lens | Dual-lens |
| Video standard | PAL (Default)/NTSC |
| Wi-Fi | Support, 2.4 G, 802.11b/g/n |
| Wired network | Support 10/100/1000 Mbps self-adaptive |
| Card capacity | 500,000 |
| Power supply | 100,000 |
| Event capacity | 150,000 |
| Face recognition accuracy rate | ≥ 99% |
| Card type | M1 card, DESfire card, Felica card |
| Card reading distance | 0 to 3 cm |
| Card reading duration | < 1 s |
| Face recognition duration | < 0.2 s per person |
| Face recognition distance | 0.3 to 3 m |

FACE RECOGNITION TERMINAL - ST673**Specifications of Face Recognition Terminal - ST673**

| | |
|----------------------------|---|
| Power supply | 12 VDC to 24 VDC/2 A |
| Working temperature | -30 °C to 60 °C (-22 °F to 140 °F) |
| Working humidity | 0 to 90% (no condensing) |
| Protective level | IP65 |
| Dimensions | 110.5 mm × 209.2 mm × 24 mm (4.35" × 8.24" × 0.94") |

**Singapore**Singapore : www.smartouch.com.sg

Office : +(65) 6396 4767 /

Mr. kenny : +(65) 9088 4767

Mr. Marco : +(65) 8122 0804

MalaysiaMalaysia : www.smartouch.com.my

Office : +607-388 9903

Mr. Kenny : 012-7883383